

## Installation instruction for KAWASAKI ZX10R 2008 ( Non-Cut ) Frame Sliders

Sitting from the bike view:

Remove Right Mid Section Cowling.

Remove Right Hand Side Bolt in Circle. ( **Picture A** )

Remove the round plastic frame cover on the frame with a flat head screw driver. ( **Picture B** )

Install the bracket which has an indication R at the back, and tighten it with Screw M10x70mm 1.25 provided. The other part should be slotted into the frame nicely. ( **Picture C** )

Install back the Mid Section Cowling.

Install the shorter frame slider to the bracket with Screw M10x40 1.5. ( **Picture D** )



Sitting from the bike view:

Remove Left Mid Section Cowling.

Remove Left Hand Side Bolt in Circle. ( **Picture A** )

Remove the round plastic frame cover on the frame with a flat head screw driver. ( **Picture B** )

Remove the Self-Locking nut in the frame, and replace with a Nut provided. ( **Picture C** )

Install the bracket which has an indication L at the back, and tighten it with Screw M10x60mm 1.25pitch provided. The other part should be tighten with Screw M10x40mm 1.25 to the frame Nut. ( **Picture D** )

Install back the Mid Section Cowling.

Install the longer frame slider to the bracket with Screw M10x40 1.5. ( **Picture E** )

